

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

CAS Number: 64-19-7 80%

Product Name: Acetic Acid 80%

 Revision Date:
 Oct 14, 2022
 Date Printed:
 Oct 14, 2022

 Version:
 1.1
 Supersedes Date:
 Jan 03, 2018

Manufacturer's Name: Thames River Chemical Corp.

Address: 5230 Harvester Road Burlington, ON, CA, L7L 4X4

Emergency Phone: CHEMTREC (800) 424-9300

Information Phone Number: 905-681-5353

Fax: 905-681-5377

Product/Recommended Uses: For laboratory or industrial use only.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Corrosive to metals - Category 1

Flammable Liquids - Category 4

Skin Corrosion - Category 1A

Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms





Signal Word

Danger

Hazardous Statements - Health

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

Hazardous Statements - Physical

H290 - May be corrosive to metals

H227 - Combustible Liquid

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P234 - Keep only in original packaging.

64-19-7 80% Page 1 of 8

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves, protective clothing, eye protection/face protection.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash/Wash hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area.
- P233 Keep container tightly closed.

Precautionary Statements - Response

- P390 Absorb spillage to prevent material damage.
- P370 + P378 In case of fire: Use carbon dixoxide, alcohol foam, water spray or dry chemical to extinguish.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P363 Wash contaminated clothing before reuse.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P310 Immediately call a POISON CENTER or doctor.
- P321 Specific treatment (see first-aid on the SDS).
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor, if you feel unwell.

Precautionary Statements - Storage

- P406 Store in a corrosive resistant container with a resistant inner liner.
- P403 Store in a well-ventilated place.
- P405 Store locked up.
- P403 + P405 Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulation. Waste management should be in full compliance with national, regional and local laws.

Physical Hazards Not Otherwise Classified

No data available.

Health Hazards Not Otherwise Classified

No data available.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000064-19-7	ACETIC ACID	80% - 80%
0007732-18-5	WATER	20% - 20%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality or to reflect batch to batch variation.

SECTION 4) FIRST-AID MEASURES

Inhalation

Get medical advice/attention if you feel unwell or are concerned. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Eliminate all ignition sources if safe to do so. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

Eye Contact

Immediately call a POISON CENTER/doctor. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 30 minutes or until medical aid is available. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical

64-19-7 80% Page 2 of 8

advice/attention.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately call a POISON CENTER/doctor. Store contaminated clothing under water and wash before re-use or discard. Rinse skin with lukewarm, gently flowing water/shower for a duration of 30 minutes or until medical aid is available.

Ingestion

Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.

Water spray or fog.

Foam.

Dry chemical powder.

BCF (where regulations permit). Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Many vapors are heavier than air. Containers may explode in fire. Many liquids are lighter than water. May form an ignitable vapor/air mixture in closed tanks or containers. Runoff to sewer may create fire or explosion hazard. Vapors may form explosive mixtures with air Vapors may travel to source of ignition and flashback Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Polymer: May polymerize explosively when heated or involved in a fire. Fire will produce irritating and corrosive gases. Contact with metals may evolve flammable hydrogen gas.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Move undamaged containers from immediate hazard area if it can be done safely. Stop spill/release if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product has a low flashpoint: Use of water spray when fighting fire may be inefficient. Large Fire: Dike fire-control water for later disposal; do not scatter the material

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Evacuate and isolate hazard area and keep unauthorized personnel away. A vapor-suppressing foam may be used to reduce vapors.

Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Do not get on skin, eyes or clothing. Avoid breathing vapor or mist.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

64-19-7 80% Page 3 of 8

Methods and Materials for Containment and Cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean, non-sparking tools to collect absorbed material. Ventilate area after clean-up is complete.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Do not get in eyes, on skin or on clothing. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. This product is not intended for human or animal consumption. Use pneumatic and/or mechanical systems for bulk transfer of the substance Use exhaust ventilation and/or dust collecting filters for bulk transfer and storage. Use approved respiratory protection when handling. Keep bulk of materials out of sewer drains. Eyewash stations and showers should be available in areas where this material is used and stored

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. Report ventilation failures immediately. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Do not store large quantities of flammable liquids in the same storage cabinet. Store in original containers. Keep containers securely sealed. Keep away from incompatible materials (e.g. oxidizers). Store flammable and combustible liquids in areas that are cool, dry and well ventilated to reduce vapour concentrations. Never use plastic or glass containers for storing flammable liquids. Keep containers securely sealed when not in use. Bond and ground metal containers/cylinders when transferring. Avoid storing in direct sunlight or near other heat sources; eliminate all sources of ignition. Cabinets must be labelled; FLAMMABLE - KEEP FIRE AWAY. Avoid storing in basements. Protect containers against banging or other physical damage when storing, transferring, or using them. Procedures must be conducted in a fume hood, glove box, or other suitable containment device. Segregate from other hazard classes and store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Provide secondary containment for toxic materials. Store, handle, and use corrosive materials in well-ventilated areas. Keep the smallest amount of material in work areas. Do not store on metal shelves. Store containers in plastic tubs or trays as secondary containment. Avoid rapid temperature changes in liquid storage areas. Store at temperatures above their respective freezing/melting point. Never store corrosives above eye level. Label cabinets with "TOXIC CHEMICALS" or similar warning.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	CANsmg	CANsppm	CANtmg	CANtppm	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)
ACETIC ACID	39	15	26	10			25	10

Chemical Name	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH TLV Basis
ACETIC ACID		1			15		10	URT & eye irr; pulm func

Chemical	ACGIH	ACGIH
Name	Carcinogen	Notations

64-19-7 80% Page 4 of 8

ACETIC ACID

func - Function, irr - Irritation, pulm - Pulmonary, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density 8.68 lb/gal Specific Gravity 1.04

Appearance clear, colourless liquid

Odor Description pungent, penetrating vinegar odour

Odor Threshold 0.07 ppm

pH 2.6 (6% solution)

Melting/Freezing Point -7.00 °C
Low Boiling Point 105.00 °C
High Boiling Point N/A
Flash Point 65.00 °C
Vapor Pressure N/A

Vapor Density 2.1 (acetic acid), 0.6 (water)

Evaporation Rate as for water
Upper Explosion Level 19%
Lower Explosion Level 5.4%
Water Solubility N/A
Coefficient Water/Oil -0.17
Viscosity N/A

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Stability

Stable under normal storage and handling conditions.

Conditions To Avoid

no data available

Hazardous Reactions/Polymerization

Hazardous polymerization will not occur.

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products

No data available.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption

64-19-7 80% Page 5 of 8

Acute Toxicity

Based on available data, the classification criteria are not met.

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

0000064-19-7 ACETIC ACID

Inhalation can irritate the nose and throat.

Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

0000064-19-7 ACETIC ACID

Contact with eyes cause burns.

Skin Corrosion/Irritation

Causes severe skin burns and eye damage

0000064-19-7 ACETIC ACID

Contact with skin causes burns.

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

May cause respiratory irritation

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Miscellaneous Health Effects

0000064-19-7 ACETIC ACID

Can cause bronchitis to develop with cough, phlegm and/or shortness of breath.

0000064-19-7 ACETIC ACID

LC50 (mouse): 2810 ppm (4-hour exposure); cited as 5620 ppm (1-hour exposure) (17)

LD50 (dermal, guinea pig): 3360 mg/kg (cited as 3.2 mL/kg) (28% solution) (24, unconfirmed)

LD50 (oral, rat): 3530 mg/kg (concentration not specified) (18)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

0000064-19-7 ACETIC ACID

Readily biodegradable.

Bioaccumulative Potential

No data available.

64-19-7 80% Page 6 of 8

Mobility in Soil

0000064-19-7 ACETIC ACID

The substance is not PBT / vPvB.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000064-19-7 ACETIC ACID

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, provincial and local laws.

SECTION 14) TRANSPORT INFORMATION

Transport Canada Information

UN number: UN2790

Proper shipping name: Acetic acid solution, not less than 50 percent but not more than 80 percent acid, by mass

Hazard class: 8
Packaging group: I

Marine Pollutant: No Data Available

Transport in bulk (according to Annex II of MARPOL 73/78): No Data Available

Note / Special Provision: No Data Available

U.S. DOT Information

UN number: UN2790

Proper shipping name: Acetic acid solution, not less than 50 percent but not more than 80 percent acid, by mass

Hazard class: 8
Packaging group: I

Hazardous substance (RQ): No Data Available Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: No Data Available

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000064-19-7	ACETIC ACID	80% - 80%	DSL,TSCA,EU_EC_Inventory - European_EC_Inventory
0007732-18-5	WATER	20% - 20%	DSL,TSCA,EU_EC_Inventory - European_EC_Inventory

64-19-7 80% Page 7 of 8

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CANsmg or CANsppm - Canadian Short Term Exposure Level in mg/L or in ppm; CANtmg or CANtppm - Canadian Time Weighted Average in mg/L or in ppm; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 1.1:

Revision Date: Oct 14, 2022

Version 1.0:

Revision Date: Mar 01, 2018

First Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

64-19-7 80% Page 8 of 8